

Interchange Range

ISO B12 Couplings



Designed and manufactured in Sheffield by PCL. This range of couplings offers excellent flow characteristics for industrial applications where this adaptor profile is required.

Key Product Benefits

- Offers enhanced tool efficiency
- Steel construction with corrosive resistant finish
- Steel shoulder prevents accidental disconnection

Specifications

Nominal bore	5.5 mm	
Flow rate @ 6bar	1100 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	500 lbf/in ²	35 bar
Interchangeability	Rectus 23/24	
	Cejn 310	
	Norgren Dynaquip DC3	
	Hanson 3000	
	US-MIL-C 4109 1/4"	
	Norgren 237	

Product Options

Part No.	Description	Thread Type	Thread Size
AC75CM	ISO B12 Coupling	Male	R 1/4
AC75EM	ISO B12 Coupling	Male	R 3/8
AC75JM	ISO B12 Coupling	Male	R 1/2
AC75CF	ISO B12 Coupling	Female	Rp 1/4
AC75EF	ISO B12 Coupling	Female	Rp 3/8
AC75JF	ISO B12 Coupling	Female	Rp 1/2
AC7506	ISO B12 Coupling	Hose Tailpiece	6mm
AC7508	ISO B12 Coupling	Hose Tailpiece	8mm
AC7510	ISO B12 Coupling	Hose Tailpiece	10mm
AC7513	ISO B12 Coupling	Hose Tailpiece	13mm