

Glycerine Gauges



All Stainless Steel Gauges, 1/4" Bottom Connection



PART NO	TYPE	CASE DIA.	CASE	WINDOW	MOVEMENT	BOURDON TUBE	CONNECTION	ENTRY	RANGE	OPERTATING TEMP.	ACCURACY
SSG63-001BG	Gly-filled	63MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/4"	0-1 bar / psi	Ambient 0-60°C	2.50%
SSG63-004BG	Gly-filled	63MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/4"	0-4 bar / psi	Ambient 0-60°C	2.50%
SSG63-012BG	Gly-filled	63MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/4"	0-12 bar / psi	Ambient 0-60°C	2.50%
SSG63-025BG	Gly-filled	63MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/4"	0-25 bar / psi	Ambient 0-60°C	2.50%
SSG63-060BG	Gly-filled	63MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/4"	0-60 bar / psi	Ambient 0-60°C	2.50%
SSG63-200BG	Gly-filled	63MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/4"	0-200 bar / psi	Ambient 0-60°C	2.50%
SSG63-400BG	Gly-filled	63MM	Polished s/s 304	Polycarbonate	s/s 304	s/s 316	s/s 304	Bottom BSPP 1/4"	0-400 bar / psi	Ambient 0-60°C	2.50%