


Aqua Paint Marker

Water-Based Temporary Marking Paint



Technical Data

AQUA PAINT MARKER is an innovative product development from Ambersil, that specifically addresses the problem of solvent discharge into the environment from traditional survey/spot marking paints.

Based on water, and removing all solvents considered harmful, **AQUA PAINT MARKER** drastically reduces solvent emissions, minimises Health & Safety concerns, and still delivers uncompromising product performance.

FEATURES

- Temporary marking paint – lasts 4 to 6 months
 - Paint is highly visible, even on dark substrates
 - Solvent content reduced by upto 35%
 - No aromatic solvents
 - Does not contain Xylene or Acetone
 - Not harmful to aquatic life
 - Non-irritant formula (EC Directive 1999/45/EC)
 - Specialist resin binding system ensures clean, clear marks
 - Can be used at all angles – ideal for ceilings, walls, and on the ground
 - No lead or other heavy metals
 - Marks can be easily removed with water and a stiff brush
 - Assists in ISO 14001 and CSR targets
 - Good operating temperature range
 - No-Purge valve – no need to waste product after use
 - One-Click™ cap – one handed operation safety cap
-
- Available in 5 fluorescent colours (Yellow, Green, Orange, Red, Blue) and matt white
 - Fluorescent for at least 1 month

APPLICATIONS

- Temporary marks for surveying, identification and construction
- Ideal for rail infrastructure maintenance (track-side)
- Perfect for utility company contractors
- Marks tunnel roofs, roadways, walls, and trees




PART NUMBERS:

32055-AA
 32051-AA
 32053-AA
 32054-AA
 32052-AA
 32050-AA



ONE-CLICK™



TECHNICAL DATA

Binder	Novel type of polymer
Water Content	Up to 35%
Solvent	IPA
Dry to Touch	5 – 10 minutes (*)
Totally Dry	25 – 35 minutes (*)
Temperature range	8°C to 50°C
Maximum Relative Humidity	85%
Packaging	500ml x 12 aerosols

(*) Depends on ambient conditions

DIRECTIONS FOR USE

- Shake aerosol well for at least 15 seconds after the agitator ball is free
- Do not apply to energised equipment
- Use only in well ventilated areas.

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 48 months with correct storage.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.