

# Industrial PAS 250 Podium Steps

## Product Dimensions

### Technical Description

Manufactured using 50mm diameter corrosion-resistant aluminium scaffold tube for use in tough construction environments. The fully-welded frames fold using durable cast aluminium components and locking castors for easy transportation.

- Tough anti-slip aluminium platform
- Impact and wear resistant 125mm nythane locking castors
- Fitted with mini stabilisers for maximum stability
- Folds flat for ease of handling and transportation

### Standards & Classification

- Max load: 150kg
- PAS250

### Warranty

5 Years



Part Number	Tread Count	Approximately Working Height* (m)	Minimum Platform Height (m)	Maximum Platform Height (m)	Open Height (m)	Closed Height (m)	Width (mm)	Width Stabilisers (m)	Open Depth (m)	Weight (kg)
LADD-1274-070	–	2.0	0.4	0.4	1.4	1.4	675	–	1.4	19.0
LADD-1274-071	–	2.1	0.5	0.5	1.5	1.5	675	–	1.4	22.0
LADD-1274-072	2	2.4	0.5	0.8	1.8	1.8	675	1.9	1.4	31.0
LADD-1274-073	3	2.6	0.8	1.0	2.1	2.1	675	1.9	1.4	33.0
LADD-1274-074	4	2.9	1.0	1.3	2.3	2.3	675	1.9	1.4	34.0
LADD-1274-075	5	3.1	1.3	1.5	2.6	2.6	950	2.2	1.4	40.0
LADD-1274-076	6	3.4	1.5	1.8	2.8	2.8	950	2.2	1.4	43.0
LADD-1274-077	7	3.6	1.8	2.0	3.1	3.1	950	2.2	1.4	46.0

### Optional Extras

Part Number	Description
1274-079	Base Plates for Podiums

### Shipping Details

Product SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Shipping Weight (gross kg)	Barcode
LADD-1274-070	1,400	250	1,400	0.4900	19.0	5060356912506
LADD-1274-071	1,500	250	1,400	0.5250	22.0	5060356912513
LADD-1274-072	1,800	250	1,400	0.6300	31.0	5060356912520
LADD-1274-073	2,100	250	1,400	0.7350	33.0	5060356912537
LADD-1274-074	2,300	250	1,400	0.8050	34.0	5060356912544
LADD-1274-075	2,600	250	1,400	0.9100	40.0	5060356912551
LADD-1274-076	2,800	250	1,400	0.9800	43.0	5060356912568
LADD-1274-077	3,100	250	1,400	1.0850	46.0	5060356912575